Printing date 09/10/2015 Revised On 09/10/2015

#### 1 Identification of the substance and manufacturer

STRIPE LIGHT BLUE TRAFFIC Trade name:

0000200648 **Product code:** 

PC9a Paints and coatings. **Product category** Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

#### 2 Hazard(s) identification

## Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

**GHS Hazard pictograms** 

**Precautionary statements** 

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:			
64742-89-8 VM&P Naphtha		24.62%	
74-98-6 propane		12.6%	
7727-43-7 barium sulfate, natur	al	7.47%	
106-97-8 n-butane		7.4%	
1317-65-3 Calcium Carbonate		6.54%	
13463-67-7 titanium dioxide		4.41%	
64742-47-8 Mineral Spirits		2.7%	
1330-20-7 xylene (mix)		1.44%	
108-65-6 PM acetate		1.09%	

## 4 First-aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.
Remove contaminated clothing. Wash exposed area with soap and water. After skin contact: After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

## 5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Special hazards:

Protective equipment for

firefighters: A respiratory protective device may be necessary.

## 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 2)

Printing date 09/10/2015 Revised On 09/10/2015

Trade name: STRIPE LIGHT BLUE TRAFFIC

Methods and material for containment and cleaning up: Ensure adequate ventilation. (Contd. of page 1)

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

7 + 30 0 proparie		
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
TLV (USA)	refer to Appendix F	

Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulfate, natural

Long-term value: 15\* 5\*\* mg/m³ \*total dust \*\*respirable fraction PEL (USA) REL (USA)

Long-term value: 10\* 5\*\* mg/m³ \*total dust \*\*respirable fraction TLV (USA) Long-term value: 5\* mg/m3

\*inhalable fraction; E

106-97-8 n-butane

74-98-6 propage

REL (USA) Long-term value: 1900 mg/m3, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppm Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL (USA) TLV (USA)

Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

## Ingredients with biological limit values:

## 1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Wash hands after use.

Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

## 9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. Not determined. Melting point/Melting range Undetermined. -44 °C (-47 °F) **Boiling point:** -19 °C (-2 °F) Flash point: Extremely flammable. Flammability (solid, gas):

**Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol % Not determined. Vapor pressure:

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

(Contd. on page 3)

(Contd. of page 2)

## Safety Data Sheet

Printing date 09/10/2015 Revised On 09/10/2015

Trade name: STRIPE LIGHT BLUE TRAFFIC

511.7 g/l / 4.27 lb/gl

VOC content: VOC content (less exempt solvents): 50.7 % Water: 19.4 %

MIR Value: 0.63 Solids content: 28.6 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

No dangerous reactions known.

Possibility of hazardous reactions: Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

## 11 Toxicological information

LD/LC50 valu	ues that are relevant for classification:
400 07 0 1-	

## 106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

## 13463-67-7 titanium dioxide

Oral LD50 >20000 mg/kg (rat) >10000 mg/kg (rbt) Dermal LD50 Inhalative LC50/4 h >6.82 mg/l (rat)

## 1330-20-7 xylene (mix)

LD50 8700 mg/kg (rat) Oral Dermal LD50 2000 mg/kg (rbt) Inhalative LC50/4 h 6350 mg/l (rat)

#### 108-65-6 PM acetate

Oral LD50 8500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

## IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide 2B 1330-20-7 xylene (mix) 3

## NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

Aquatic toxicity: Persistence and degradability: Hazardous for water, do not empty into drains.

The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

#### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

## 14 Transport information

**UN-Number** UN1950 DOT UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable 1950 Aerosols

**ADR** Transport hazard class(es):

Class Marine pollutant: No

Special precautions for user: Warning: Gases

F-D,S-Ŭ EMS Number:

**Packaging Group: UN "Model Regulation":** UN1950, Aerosols, 2.1

# **Safety Data Sheet**

Printing date 09/10/2015 Revised On 09/10/2015

Trade name: STRIPE LIGHT BLUE TRAFFIC

(Contd. of page 3)

		(** ** 1 * 3 * */		
15 Regulatory information				
SARA Section 355 (extremely hazardous substances):				
None of the ingredients in this product are listed.  SARA Section 313 (Specific toxic chemical listings):				
1330-20-7 xylene (mix)				
CPSC:	This product complies with 16 CFR 1303 and does not contain	more than 90 ppm of lead.		
California Proposition 65 chemicals known to cause cancer:				
13463-67-7 titanium dioxide				
100-41-4 ethyl benzene				
CANADIAN ENVIRONMENTAL PROTECTION ACT:  All hazardous ingredients for this product appear on the Canadian Domestice Substance List.				
EPA:				
7727-43-7 barium sulfate, natural		D, CBD(inh), NL(oral)		
1330-20-7 xylene (mix)				

16 Other information
Contact:
Date of preparation / last revision Regulatory Affairs 09/10/2015 / -