

Safety Data Sheet

Page 1/4

Printing date 12/11/2015

Revised On 12/11/2015

1 Identification of the substance and manufacturer

Trade name: 241 SILVER ATHLETIC FIELD MARKER
Product code: MO00200241
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: MISSOURI TURF PAINT
 1201 E. 63RD STREET
 KANSAS CITY MO 64110
 Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H335 May cause respiratory irritation.

GHS Hazard pictograms



GHS02 GHS04 GHS07

Signal word

Hazard statements

Precautionary statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 May cause respiratory irritation.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Wear protective gloves.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of water.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Protect from sunlight. Store in a well-ventilated place.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1317-65-3	Calcium Carbonate	16.45%
74-98-6	propane	12.6%
142-82-5	heptane	10.45%
64742-89-8	VM&P Naphtha	8.6%
106-97-8	n-butane	7.4%
64742-47-8	Mineral Spirits	5.22%
13463-67-7	titanium dioxide	4.15%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

(Contd. on page 2)

Safety Data Sheet

Page 2/4

Printing date 12/11/2015

Revised On 12/11/2015

Trade name: **241 SILVER**

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F in TLVs and BEIs book

142-82-5 heptane

REL (USA) Long-term value: 2000 mg/m³, 500 ppm

REL (USA) Long-term value: 350 mg/m³, 85 ppm

Ceiling limit value: 1800 mg/m³, 440 ppm

□ 15-min

TLV (USA) Short-term value: 2050 mg/m³, 500 ppm

Long-term value: 1640 mg/m³, 400 ppm

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Appearance:

Aerosol.

Odor:

Solvent

Odor threshold:

Not determined.

pH-value:

Not determined.

Melting point/Melting range

Undetermined.

Boiling point:

-44 °C (-47 °F)

Flash point:

-19 °C (-2 °F)

Flammability (solid, gas):

Extremely flammable.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit:

1.1 Vol %

Upper Explosion Limit:

10.9 Vol %

Vapor pressure:

Not determined.

Relative Density:

Between 0.77 and 0.85 (Water equals 1.00)

Vapour density

Not determined.

Evaporation rate

Not applicable.

Partition coefficient: n-octanol/water:

Not determined.

Solubility:

Not determined.

Viscosity:

Not determined.

VOC content:

470.9 g/l / 3.93 lb/gal

VOC content (less exempt solvents):

45.5 %

Water:

27.0 %

MIR Value:

0.53

Solids content:

26.2 %

10 Stability and reactivity

Reactivity:

Stable at normal temperatures.

Conditions to avoid:

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

Chemical stability:

Not fully evaluated.

(Contd. on page 3)

Safety Data Sheet

Page 3/4

Printing date 12/11/2015

Revised On 12/11/2015

Trade name: 241 SILVER

(Contd. of page 2)

Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

13463-67-7 titanium dioxide

Oral LD50 >20000 mg/kg (rat)

Dermal LD50 >10000 mg/kg (rbt)

Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: No irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide

2B

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Ecotoxic effects:
Remark: Toxic for fish
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT N/A
DOT Consumer Commodity ORM-D
 Aerosols, flammable
ADR 1950 Aerosols, ENVIRONMENTALLY HAZARDOUS
Transport hazard class(es):
Class 2.1
Marine pollutant: Yes
Symbol (fish and tree)
Special marking (ADR): Symbol (fish and tree)
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Quantity limitations On passenger aircraft/rail: 75 kg
 On cargo aircraft only: 150 kg

ADR
Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

(Contd. on page 4)

Safety Data Sheet

Page 4/4

Printing date 12/11/2015

Revised On 12/11/2015

Trade name: 241 SILVER

(Contd. of page 3)

100-41-4	ethyl benzene
1333-86-4	Carbon black
CANADIAN ENVIRONMENTAL PROTECTION ACT:	
All hazardous ingredients for this product appear on the Canadian Domestic Substance List.	
EPA:	
142-82-5	heptane
	D

16 Other information

Contact: Regulatory Affairs
Date of preparation / last revision 12/11/2015 / -