Safety Data Sheet

Printing date 12/11/2015 Revised On 12/11/2015

1 Identification of the substance and manufacturer

Trade name: **627 BLUE TEMPORARY EVENT MARKER**

MO00200627 Product code:

Product category PC9a Paints and coatings. Manufacturer/Supplier: MISSOURI TURF PAINT 1201 E. 63RD STREET

KANSAS CITY MO 64110 Phone: 815-895-9101 www.seymourpaint.com CHEMTEL 1-800-255-3924, or 813-248-0585.

Emergency telephone number:



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eve Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep away from near/sparks/open flames/not surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Protect from sunlight. Store in a well-ventilated place.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description This product is a mixture of the substances listed below with nonhazardous additions

enomical Becompation.		The product of a mixture of the cubotanece listed below with normazardede additione.	
Dangerous components:			
67-64-1	Acetone		25.46%
67-63-0	isopropyl alcohol		19.5%
1317-65-3	Calcium Carbonate		17.85%
74-98-6	propane		17.61%
106-97-8	n-butane		10.34%
2807-30-9	Glycol Ether EP		3.86%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

doctor. Rinse mouth with water. Do not induce vomiting.

After swallowing: Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Can form explosive gas-air mixtures.

Protective equipment for

firefighters: A respiratory protective device may be necessary.

(Contd. on page 2)

Printing date 12/11/2015 Revised On 12/11/2015

Trade name: BLUE TEMPORARY EVENT MARKER

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. Storage requirements:

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm Long-term value: 590 mg/m³, 250 ppm REL (USA) Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI TLV (USA)

67-63-0 isopropyl alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm REL (USA) Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm TLV (USA)

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs and BEIs book

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

67-63-0 isopropyl alcohol

BEI (USA) 40 mg/L Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

Immediately remove all soiled and contaminated clothing. Hygienic protection:

Wash hands after use. Avoid contact with the eyes and skin.

Do not eat or drink while working. **Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol

Odor: Solvent

Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Boiling point: Undetermined.

Flash point:

-19 °C (-2 °F) Extremely flammable.

Flammability (solid, gas): Decomposition temperature:

Not determined

-44 °C (-47 °F)

Auto igniting:

Product is not self-igniting.

Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: Upper Explosion Limit:

1.5 Vol % 12.0 Vol %

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 12/11/2015 Revised On 12/11/2015

Trade name: BLUE TEMPORARY EVENT MARKER

Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Viscosity: Not determined. **VOC** content: 563.1 g/l / 4.70 lb/gl 52.2 %

VOC content (less exempt solvents): 0.4 % Water: MIR Value: 0.69 Solids content: 218%

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known. Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 isopropyl alcohol

LD50 4570 mg/kg (rat) Dermal LD50 13400 mg/kg (rab) Inhalative LC50/4 h 30 mg/l (rat)

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

67-63-0 isopropyl alcohol

NTP (National Toxicology Program) None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Persistence and degradability:

Hazardous for water, do not empty into drains. The product is easily degradable. However, a residual mark may remain. The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A

Consumer Commodity ORM-D Aerosols, flammable DOT

ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Marine pollutant: No

Warning: Gases F-D,S-U Special precautions for user:

EMS Number:

Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

ADR

Excepted quantities (EQ)

Not permitted as Excepted Quantity

(Contd. on page 4)

I

Safety Data Sheet

Printing date 12/11/2015 Revised On 12/11/2015

Trade name: BLUE TEMPORARY EVENT MARKER

(Contd. of page 3)

IMDG Limited quantities (LQ)

Excepted quantities (EQ)

Packaging Group: UN "Model Regulation": Code: E0 Not permitted as Excepted Quantity

UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 isopropyl alcohol

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

EPA:

16 Other information

67-64-1 Acetone

Contact: Regulatory Affairs Date of preparation / last revision 12/11/2015 / -