

Safety Data Sheet

Page 1/4

Printing date 12/11/2015

Revised On 12/11/2015

1 Identification of the substance and manufacturer

Trade name: 628 WHITE TEMPORARY EVENT MARKER
Product code: MO00200628
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: MISSOURI TURF PAINT
 1201 E. 63RD STREET
 KANSAS CITY MO 64110
 Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

GHS Hazard pictograms



GHS02 GHS04 GHS07

Signal word

Hazard statements

Precautionary statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 May cause respiratory irritation. May cause drowsiness or dizziness.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a POISON CENTER/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Protect from sunlight. Store in a well-ventilated place.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	23.91%
1317-65-3	Calcium Carbonate	17.98%
74-98-6	propane	17.64%
67-63-0	isopropyl alcohol	15.0%
106-97-8	n-butane	10.36%
13463-67-7	titanium dioxide	3.89%
2807-30-9	Glycol Ether EP	3.36%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

(Contd. on page 2)

Safety Data Sheet

Page 2/4

Printing date 12/11/2015

Revised On 12/11/2015

Trade name: WHITE TEMPORARY EVENT MARKER

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F in TLVs and BEIs book

67-63-0 isopropyl alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm

REL (USA) Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV (USA) Short-term value: 984 mg/m³, 400 ppm

Long-term value: 492 mg/m³, 200 ppm

BEI

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

67-63-0 isopropyl alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Appearance:

Aerosol.

Odor:

Solvent

Odor threshold:

Not determined.

pH-value:

Not determined.

Melting point/Melting range

Undetermined.

Boiling point:

-44 °C (-47 °F)

Flash point:

-19 °C (-2 °F)

Flammability (solid, gas):

Extremely flammable.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit:

1.5 Vol %

Upper Explosion Limit:

12.0 Vol %

(Contd. on page 3)

Safety Data Sheet

Page 3/4

Printing date 12/11/2015

Revised On 12/11/2015

Trade name: WHITE TEMPORARY EVENT MARKER

(Contd. of page 2)

Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapour density: Not determined.
Evaporation rate: Not applicable.
Partition coefficient: n-octonal/water: Not determined.
Solubility: Not determined.
Viscosity: Not determined.
VOC content: 539.0 g/l / 4.50 lb/gl
VOC content (less exempt solvents): 47.3 %
Water: 2.3 %
MIR Value: 0.66
Solids content: 26.4 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 isopropyl alcohol

Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

106-97-8 n-butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

13463-67-7 titanium dioxide

Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rht)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

67-63-0	isopropyl alcohol	3
13463-67-7	titanium dioxide	2B

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is easily degradable. However, a residual mark may remain.
The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number: UN1950
DOT: N/A
DOT: Consumer Commodity ORM-D
Aerosols, flammable
1950 Aerosols
ADR:
Transport hazard class(es):
Class: 2.1
Marine pollutant: No
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U

(Contd. on page 4)

Safety Data Sheet

Page 4/4

Printing date 12/11/2015

Revised On 12/11/2015

Trade name: WHITE TEMPORARY EVENT MARKER

Quantity limitations

On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

(Contd. of page 3)

ADR

Excepted quantities (EQ)

Code: E0
Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E0
Not permitted as Excepted Quantity

Packaging Group:

--

UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 isopropyl alcohol

CPSC:

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1 Acetone

16 Other information

Contact:

Regulatory Affairs

Date of preparation / last revision

12/11/2015 / -